

PlayGuard is manufactured by Ecore. Since 1871, Ecore has been transforming reclaimed waste into unique surfaces that make people's lives better. What started with simple cork closures has evolved into a diverse portfolio of products solving complex problems in applications ranging from playgrounds, weight rooms, and turf fields to hospitals, hotels, and retail environments. We are driven everyday by a simple question, "Can a floor do more?" At Ecore, we believe the answer is "YES." We are building our company and the products we offer based on the simple notion that surfaces should elevate beyond current expectations. Our energy is focused on the interaction between people and the surface. We engineer performance well beyond industry standards related to acoustics, ergonomics, and safety. Harvesting the unique power from a myriad of waste streams, Ecore creates products that align-substantial force reduction with a balanced amount of energy return to create dynamic surfaces that are catered to the individual and the application.

ecore

Built by Yes.

People will fall... we will be there to catch them! Professionals will overwork their bodies... we will soften the blow! Footfall sounds will keep someone awake... we will guiet the noise!

PlayGuard is FloorScore **Certified for Indoor Use**



ы **OSCS**certified.

This product has been certified to meet the requirements of the flooring products certification program for indoor air quality.



SCS-FS-01793

Ecore reserves the right to make updates to this catalog at any time. For the most updated version, or for more informaiton, please visit playguardsurfacing.com or call 800.851.4746.





Characteristics

- 24" x 24" modular tiles in four thicknesses for choices in impact resistance and cost
- Factory molded to ensure consistent fall height protection and uniform appearance
- Patented, pre-manufactured colorful Ultra wear laver (1", 2-1/2", and 4-1/4")
- Meets 2', 6', 8', and 10' critical fall height requirements per ASTM F1292-13 and is CPSC compliant
- Slip resistant for wet or dry surfaces
- · Resilient, comfortable surface encourages play
- · Tiles won't crack, eliminating unsightly surface repairs

- Will not shift or displace during play
- Meets ADA standards
- Extremely durable for low life-cycle
- Easy to clean, low-maintenance surface
- Unlikely to conceal sharp or potentially harmful objects
- · Individual tiles can be removed and replaced if damaged
- Custom colors, logos, and designs available for PlayGuard Ultra
- · Made in the U.S.A. from the highest quality recycled rubber







Sustainability

Creating Sustainable Environments

Ecore is the largest user of scrap tire rubber in the U.S.A., converting more than 65 million pounds of tires annually into recycled rubber flooring. With our state of the art equipment, experienced staff, and 100 million pound capacity, Ecore is uniquely capable of producing the cleanest, most consistent, and highest quality material available in the market place.



Floor Score

Indoor PlayGuard applications are FloorScore certified for compliance with rigorous indoor air quality emission requirements.



CHS SCHOOLS

PlayGuard meets the Collaborative for High Performance Schools (CHPS) criteria, the state of Washington standard for indoor air quality, and supports ASTM 2129-05 Sustainability Assessment.



LEED

CHPS

PlayGuard can contribute toward earning up to 8 LEED points. For information on how PlayGuard can contribute to LEED points please visit PlayGuardSafetySurfacing.com.



Applications

- Playgrounds
- Rooftops
- Patios Recreation spaces
- Daycare & after-school activity grounds
- Rehabilitation centers
- Schools

Carnival Ultra








Cherry Blast 2 PG61A



Caramel Corn 2 PG66A



Grape Slushie PG78

Used in combination or as single color accents, the wear layer colors of the Carnival Ultra line create bright and engaging atmospheres that beg for participation and activity. This collection's vivid patterns bring design themes to life and transform playgrounds into lively community attractions. Carnival Ultra tiles are manufactured with proprietary processes that mold a dense recycled rubber and EPDM wear layer, which is 3mm thick, to a footed recycled rubber base.

*Actual sample and final product may vary from color swatches shown in this catalog.



Blueberry Pie 2 PG62A



Funnel Cake 2 PG67A



Specifications

Tiles: 24" x 24" Thicknesses: 1", 2.5", & 4.25"




Sour Apple 2 PG63A

PG61B PG62B PG63B PG65B PG66B PG67B PG76A PG77A PG78A




Rock Candy 2 PG65A





Safari Ultra




Midnight PG50

Zappy Zebra PG52



Bumble Bee PG72



Ladybug PG74

Red Fox PG75

Specifications

Tiles: 24" x 24" Thicknesses: 1", 2.5", & 4.25"

Recommended Accessory Colors

PG40A



Pigmented

If color isn't a primary consideration, budgets are tight, or simplistic design is the focus, Pigmented tiles are the ideal solution! Manufactured without an EPDM wear layer, the earth-tone hues of the Pigmented collection are produced by evenly distributing pigment throughout the rubber tile.

Custom color and logo options are not available for pigmented tiles.





Specifications

Recommended Accessory Colors

PG40A PG41A PG42A PG43A

Tiles: 24" x 24" Thicknesses: 1", 2.5", & 3.75"

Swing Mats



Black PG40 (Non-Pigmented)



Grey PG41



Red PG42



Green PG43

* Pigmented tiles are **not** recommended for indoor use.



PlayGuard Swing Mats are loose lay and can easily be installed under swing sets and at the feet of sliding boards. Swing Mats do not carry a fall height rating and are only recommended to help prevent the spread of wood mulch, pea gravel, or rubber crumb.

Available in black only.

Specifications


Tiles: 36" x 36" Thicknesses: 1.5"





Accessories


1" Carnival Ultra, Safari Ultra, & Pigmented




48"×4"×1"

3.125" × 1/4"

2½" Carnival Ultra, Safari Ultra, & Pigmented




48" × 8" × 2-1/2""



24" × 24" × 2-1/2" (2)



L/R Side Reducer for ADA Access Ramp 24" × 8" × 2-1/2"




Outside 90 Corner Reducer 16" × 8" × 2-1/2"




Outside 45 Corner Reducer 16" × 8" × 2-1/2"



Inside 45 Corner Reducer 12" × 8" × 2-1/2"




Inside 90 Corner Reducer 12" × 8" × 2-1/2"




Quad Blok Connector 8" x 8" x 17 mm

4¼" Carnival Ultra, Safari Ultra




Reducer 48" × 12" × 4-1/4"



ADA Access Ramp 48" x 19-3/4" (2) Custom order only




Large Quad Blok Connector 8.75" x 8.75" x 19mm




3¾" Pigmented

48" × 12" × 3-3/4"



ADA Access Ramp 48" x 19-3/4" (2) Custom order only



Large Quad Blok Connector 8.75" x 8.75" x 19mm


Accessory Colors

















Caramel Corn 2 PG66B Funnel Cake 2





Grape Slushie PG78A

Rock Candy 2 PG65B



Custom Colors





Actual sample and final product may vary from color

swatches shown in this catalog.

Creative Recreational Systems, Inc. | www.CreativeSystems.com | 877-752-9797

Create playful patterns using distinctly colored tiles or make a bold statement with custom designs created to complement any project's theme.

Custom logos and designs can be created with any combination of Carnival Ultra, Safari Ultra, or custom colors and are manufactured as a part of the tile's wear layer for long-lasting patterns that don't flake, chip, or peel.













Live to Play

PlayGuard Safety Surfacing's Live to Play Program is a creative way to bring active play to your playground through designs in the surface. Through our patented tile technology, we are able to cut inlaid water-jet designs directly into the surface of the tile using precise detail that is not currently available through traditional tile and poured-in-place products. You may choose from our Live to Play portfolio of existing inspirational ideas designed to spark your imagination, or work with PlayGuard and our partners to design your own custom surface.

When choosing directly from our Live to Play product portfolio, all artwork, proofing, and pricing has already been done in advance and allows you to expedite your bidding process, while still achieving a truly custom look.

Options

- Foursquare
- · Hopscotch: Simple
- · Hopscotch: Extreme
- · Checkers Board
- Baseball
- Basketball
- Football Footprints
- · Soccer Ball
- · Tennis Ball
- Runner
- 50 States




Benefits

- · Features a patented, water jet cut tile system
- 15 year warranty
- Standard and custom graphic options
- Endless color options
- · Unsurpassed graphic detail quality
- Compliment play equipment using new and engaging activities












Please contact your distributor for additional designs or visit playquardsurfacing.com.

Quad BlokTM



Ideal for playgrounds, rooftops, and patios, our exclusive Quad BlokTM system offers reliable easy-down/easy-up installations. Quad Blok connectors are made of high quality, post-consumer tire rubber and polyurethane. Unlike labor intensive poured-in-place systems, Quad Blok modular connectors feature precisely located multiple openings that interface with the corner leg understructure of PlayGuard tiles. These connectors are quick and easy to use without adhering to or causing damage to playground substrates. If an individual tile ever does need replacement, removing and securing a new tile causes minimal disruption or downtime.





NOTE: ONE QUAD BLOK PER TILE IS REQUIRED

Property	Test Method	Typical Result
Density	ASTM D297	45-lbs./cu.ft.³min.
Tensile Strength	ASTM D412, DIE C	100psi. min.
Elongation	ASTM D412, DIE C	65% min.
Compression	ASTM F36	Recovery
@50psi	15%	80%
@100psi	28%	90%
@200psi	45%	95%
Shore A Hardness	ASTM D2240	50 +/- 5 points
Tear Strength	ADTM D624, DIE C	30-lbs.f/in
Flexibility	ASTM F147	0-1 Factor
Compression Set B 25% deflection, 22 hrs. 158°F	ASTM D395	25%
Compression Set (Foam) 50% deflection, 22 hrs. 158°F	ASTM D3676	20%

Features:

- · Available in 2 sizes:
- -8" x 8" x 17mm for 2-1/2" Tiles
- -8.75" x 8.75" x 19mm for $3\frac{3}{4}$ " and $4\frac{1}{4}$ " tiles
- 15 year warranty
- Recycled rubber and polyurethane composition
- · Highly durable
- Enables rooftop installation capabilities
- · Eliminates damage to the roofing membrane
- · Allows rapid water drainage around each tile
- Ample void under tiles for water drainage flow

Rooftops & Patios



PlayGuard Safety Surfacing is ideal for rooftop and patio applications due to its unique Quad Blok installation system and cushioned resilience. With the Quad Blok system, PlayGuard tiles are attached to the connector and not the roof itself. This eliminates costly damage to elastomeric membranes and ensures that the quality of the roof remains unaltered. ColorMill® EPDM allows for greater UV fade resistance compared to other EPDM rooftop and patio applications.

PlayGuard tiles also allow for water drainage. The superior design of PlayGuard, in combination with the connector system, ensures that water will quickly reach the roof surface and flow to drains, avoiding ponding and enabling easy maintenance. The tiles' superior durability and non-slip properties make them ideal for areas prone to direct exposure to the natural elements and, with the Quad Blok installation system, damaged tiles can be easily removed or replaced.





Technical Specifications

Critical Fall Height and Physical Dimensions				
Thickness	Weight (lbs.) Each (Not less than)		Critical Fall Height (ft.)	
	Pigmented	Carnival & Safari	Pigmented	Carnival & Safari
1"	16	16	2.0	2.0
2-1/2"	25	27	6.0	6.0
3-3/4"	34	N/A	8.0	N/A
4-1/4"	N/A	39	N/A	8.0
2-1/2 & 2-1/8" Polyfoam	27	29	10.0	10.0

	Packaging Information				
	Full Pallet Weight (lbs.)				
Thickness	Pieces/Pallet	Pigmented	Carnival & Safari	Pallet Height	Other Packaging Information
1"	120	1,980	1,980	35.00"	
2-1/2"	100	2,560	2,760	66.00"	
3-3/4"	60	2,100	N/A	62.00"	Standard Pallet Size: 48"x48"
4-1/4"	60	N/A	2,400	68.00"	Empty Pallet Weight: 60 lbs
2-1/8" x 4' x 6' (Polyfoam Sheet)	23	680	680	52.00"	Standard Pallets in 48' Van: 20

Physical Data Test			
Characteristic	Test Method	Pigmented Tile	Carnival & Safari Tile
Density	ASTM D297	50 lb./ft³ min.	70 lb./ft³ min.
Tensile Strength*	ASTM D412, DIE C	150 lb./in² min.	180 lb./in² min.
Elongation at Break*	ASTM D412, DIE C	50% min.	70% min.
Abrasion Test*	ASTM D3389	Less than 0.010" lost	Less than 0.010" lost
Coefficient of Friction*	ASTM D2047	0.8 min.	0.8 min.
Flammability	ASTM D2859 (Burning Pill Test)	8 of 8 samples passed	8 of 8 samples passed
Wheel Chair Accessibility	ASTM F1951-08	Pass	Pass
Lead Content	US EPA Method 3052:1996	Pass	Pass

FIFTEEN YEAR LIMITED WARRANTY INFORMATION - Materials, Workmanship, and Performance		
Number of years from date of original installation to date of claim	Percentage of product purchase price found to be defective or non-compliant	
0-6	100%	
More than 6, but less than 7	60%	
More than 7, but less than 8	40%	
More than 8, but less than 9	30%	
More than 9, but less than 10	20%	
More than 10, but less than 12	10%	
More than 12, but less than 15	5%	





On: Facebook | Twitter | Instagram | YouTube | LinkedIn | Pinterest | Google +